

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
21 December 2000 (21.12.2000)

PCT

(10) International Publication Number
WO 00/77433 A1

(51) International Patent Classification: F16L 11/12, 35/00

(21) International Application Number: PCT/IB00/00778

(22) International Filing Date: 10 June 2000 (10.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
VI99A000120 10 June 1999 (10.06.1999) IT

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): EURO-CONDOTTE S.P.A. [IT/IT]; Corso Palladio, 42, I-36100 Vicenza (IT).

Published:

— With international search report.


(72) Inventor; and

(73) Inventor/Applicant (for US only): MEZZALANA, Riccardo [IT/IT]; Via Breganzola, 3, I-36057 Arcugnano (IT).

(74) Agent: MAROSCIA, Antonio; Maroscia & Associati S.r.l., Corso Palladio, 42, I-36100 Vicenza (IT).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: REINFORCED FLEXIBLE HOSE AND METHOD FOR THE PRODUCTION THEREOF



(57) Abstract: A reinforced flexible hose (1) comprising at least a first inner extruded tubular layer (3) and at least a second extruded tubular layer (2) with a tubular reinforcement fabric (4) provided between said first (3) and second (2) hoses. The two tubes are joined so as to form a homogeneous unit by their mutual contact surfaces, by gluing or molecular adhesion for example. The end portion of the hose (1) increases in width so much as to make it possible to achieve a better mechanical hold with the standard junctions to which it is bound to be fixed. The thickness increases at the end portions may either be constant along its whole length, or start gradually toward the end.

WO 00/77433 A1